

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claims 1-6 (Canceled).

7. (Original) A method of a wireless transmission, wherein said method comprises:

transmitting a first signal to a first wireless network interface and sending said first signal by using said first wireless network interface;

receiving said first signal by using a second wireless network interface and transmitting said first signal to a microprocessor;

transforming said first signal to become a second signal and transmitting said second signal to a bridge;

transmitting said second signal from said bridge to a device;

sending a third signal from said device and transmitting said third signal to said bridge;

transmitting said third signal from said bridge to said microprocessor;

transforming said third signal to become a fourth signal and transmitting said fourth signal to said second wireless network interface;

sending said fourth signal; and

receiving said fourth signal by using said first wireless network interface.

8. (Original) The method according to claim 7, wherein said first signal is a wireless signal.

9. (Original) The method according to claim 7, wherein said fourth signal is a wireless signal.

10. (Original) The method according to claim 7, wherein said first wireless network interface is located in a mobile computer.

11. (Original) The method according to claim 7, wherein said second wireless network interface is located in a foundation.

12. (Currently Amended) A method of a wireless transmission, wherein said method comprises:

- opening a power of a mobile computer;
- detecting a wireless signal which is sent out from a foundation;
- building a flag in a basic input/output system of said mobile computer;
- executing [[a]] an operating system of said mobile computer;
- detecting said flag;
- showing a sign on a monitor of said mobile computer;
- transmitting a first signal to a first wireless network interface and sending said first signal by using said first wireless network interface;
- receiving said first signal by using a second wireless network interface and transmitting said first signal to a microprocessor;
- transforming said first signal to become a second signal and transmitting said second signal to a bridge;
- transmitting said second signal from said bridge to a device;
- sending a third signal from said device and transmitting said third signal to said bridge;
- transmitting said third signal from said bridge to said microprocessor;
- transforming said third signal to become a fourth signal and transmitting said fourth signal to said second wireless network interface;
- sending said fourth signal; and
- receiving said fourth signal by using said first wireless network interface.

13. (Original) The method according to claim 12, wherein said first signal is a wireless signal.

14. (Original) The method according to claim 12, wherein said fourth signal is a wireless signal.

15. (Original) The method according to claim 12, wherein said microprocessor is located in said foundation.

16. (Original) The method according to claim 12, wherein said bridge is located in said foundation.

17. (Original) The method according to claim 12, wherein said operating system comprises a driver, which can drive said first wireless network interface.

18. (Original) The system according to claim 12, wherein a protocol of said first wireless network interface and a protocol of said second wireless network interface are the same.